

Pallet: generic and customizable pallet, Layers and covers



Jollyplast s.r.l. develops generic black and colored pallet for its automated handling layers in HDPE and in ABS materials

Starting from a pallet having the height fixed in 150 mm from the ground for the use with the transpallet on 4 sides, later, the other 2 dimensions X and Y are free adaptable to the customer needs starting from the dimension of mm 600x600 until mm 1400x1400



It is easy to insert a layer on pallet and this operation is free of error with Jollyplast automated handling layers with rotation on 180°. The rotation correctness is guaranteed by the coloured stripe on one side of the layer

The pallet is guaranteed until 4000 kg in static use and it is designed to be coupled with the Jollyplast automated handling layers. The pallet, the layers and the cover are designed to be handled by steel, plastic and fibre strap





The cover for the pallet is designed to fit over the automated handling layers in a so perfect way that it is possible to position a second pallet level over the first one in a stable and checked way

The X and Y dimensions are extremely customizable mainaning the initial load guarantees and the general working methods with the rivetted layers, with the groove method and with the glue method (only with ABS pallet and layer)



The layers have automated handling method so that they are automatically packed at the right distance one from the other during the transportation from one place to one other during both the steps of the load and unload

The protection of the objects and the guarantee of precision are the Jollyplast s.r.l. secrets: in every situation, even the most critical.
**Your work is immune from accidents.
Ever.**

